

Description

Profile® II filters are all polypropylene. The elements have an absolute-rated downstream section, and a continuously graded pore size upstream section, which increases service life many-fold.

The materials of construction - chemically resistant polypropylene - permit application in a very wide range of corrosive and non-corrosive fluids. The fibers in Profile II filters may be considered continuous. No binder resin is used - the fibers are "bonded" by intertwining during the manufacturing process. As a result, Profile II filters show no media migration.

The Profile II filter has numerous applications in a broad range of industries that include chemical, petrochemical, photochemical, pharmaceutical, biological, electronic, magnetic tape, electroplating, food and beverage, cosmetic, veterinary, medical and fermentation industries. They are used as both prefilters and as final filters.



Standard Profile® II Filter Elements. Available in RF Series, RMF Series and AB Series—Code 3 and Code 7.

Operating Characteristics

Recommended maximum pressure differential is 60 psi up to 30°C (86°F), 50 psi up to 50°C (122°F), 30 psi up to 70°C (158°F), and 15 psi up to 82°C (180°F).

For applications where the filters are heated for any reason above 122°F (50°C) and the temperature is then reduced by 36°F (20°C) or more, AB Series elements are recommended. See Bulletin PRO 400 and PRE-1 for more detailed information.

Table I. Profile II Cartridge Grades And Their Characteristics

Cartridge Grade	Removal Ratings		Gaseous Service DOP (0.3 µm) ⁽¹⁾ Efficiency %	Typical Clean Pressure Drop		Typical Aqueous Flow (GPM/10" Cartridge)
	Liquid Service Rating in µm At % Efficiency 99.9%	% Efficiency 100%		Liquid Service Aqueous Pressure drop ⁽²⁾	Gaseous Service CFM of air per PSI per 10" cartridge ⁽³⁾	
003*	<0.5 ⁽⁴⁾	<0.5 ⁽⁴⁾	>99.9999	3.5	2.3	1 - 2.5
005	<0.5 ⁽⁴⁾	<0.5 ⁽⁴⁾	>99.9999	2.8	2.7	1 - 2.5
010	<0.5 ⁽⁴⁾	1	>99.9999	2.6	3.6	1 - 3
030	2.5	3	>99.9999	1.5	6.4	2 - 5
050	4	5	>99.9999	0.8	11.0	3 - 8
070	6	7	>99.9999	0.5	17.0	5 - 12
100	9	10	99.2	0.3	29.0	6 - 15
120	11	12	96.5	0.2	36.0	6 - 15
150	13	15	88	0.15	44.0	8 - 15
200	18	20	84.8	0.10	75.0	10 - 15
300	26	30	67	0.08	119.0	10 - 15
400	35	40	48.3	0.05	207.0	10 - 15
700	70	— ⁽⁵⁾	34	<0.05	415.0	10 - 15
900	90 ⁽⁴⁾	— ⁽⁵⁾	25	<0.05	640.0	10 - 15
1200	120 ⁽⁴⁾	— ⁽⁵⁾	10	<0.05	1000.0	10 - 15

⁽¹⁾ Air flow used for these data was 20 cfm/10" module, except grade 700, which was run at 4 cfm.

⁽²⁾ Pressure drop is PSI per GPM for a single 10" module. For multiple elements, divide by number of modules. For fluids other than water, multiply by viscosity in centipoise.

⁽³⁾ For longer modules, increase the flow rates listed in proportion. The flow rates

listed do not take into account pressure losses due to flow in the internal diameter of the element, which becomes significant above about 40 to 60 cfm.

⁽⁴⁾ Extrapolated values.

⁽⁵⁾ Precise evaluation of the 100% removal efficiency for these coarse grades is not possible with test procedure utilized.

* AB style only.

Sizes

The Profile II RF, and RMF Series filter elements are 2½" O.D. and are available in one piece 10", 20", 30", and 40" length modules. Profile II elements are also available in 2¾" diameter

AB Code 3, 7 and 8 Series configurations. See Bulletin PRO 400 for further details.

Part Numbers / Ordering Information

Table II. Standard Configurations of Profile II Cartridges

100% Removal Rating, μm	Profile II Element Part Numbers	
	For General Application	For General Application Including in situ Steam Sterilization, and in situ Hot Water Sanitizing ⁽¹⁾
	RF Series	AB Series
0.3* ⁽²⁾		AB ▲ Y003 ◆ ▼ ☆
0.5 ⁽²⁾	R ■ ▲ F005 ●	AB ▲ Y005 ◆ ▼ ☆
1	R ■ ▲ F010 ●	AB ▲ Y010 ◆ ▼ ☆
3	R ■ ▲ F030 ●	AB ▲ Y030 ◆ ▼ ☆
5	R ■ ▲ F050 ●	AB ▲ Y050 ◆ ▼ ☆
7	R ■ ▲ F070 ●	AB ▲ Y070 ◆ ▼ ☆
10	R ■ ▲ F100 ●	
12	R ■ ▲ F120 ●	
15	R ■ ▲ F150 ●	
20	R ■ ▲ F200 ●	
30	R ■ ▲ F300 ●	
40	R ■ ▲ F400 ●	
70	R ■ ▲ F700 ●	
90	R ■ ▲ F900 ●	
120	R ■ ▲ F1200 ●	

■		▲		●		▼		☆	
Gasket	Code	Nominal Length, In.	Code	Gasket Material	Code	Application	Code	O-ring Option	Code
None	No Symbol	10	1	Alloy of Polypropylene and Ethylene Propylene Diene Monomer (EPDM)	H21	Pharmaceutical	P	Silicone	H4
Elastomeric Material**	M***	20	2			Other	Omit	Viton A	H
		30	3					Ethylene-Propylene	J
		40	4						

Cartridge Diameter O.D., In.	Adaptor Configuration	Number of O-rings	O-ring Size	FDA Listed Materials of Construction	Code
2 $\frac{3}{4}$	Flat Top	2	222	Yes	3
2 $\frac{3}{4}$	Finned Top, Locking Tabs	2	226	Yes	7
2 $\frac{3}{4}$	Finned Top	2	222	Yes	8

⁽¹⁾ Only P grade AB Series elements may be in-situ steam sterilized.

⁽²⁾ Extrapolated valves.

* AB style only.

** Provides a positive sealing surface to eliminate potential fluid bypass in competitive housings with blunt knife edges.

*** When the M symbol is selected the part number must end in H21 code.

Table III. Housings For Profile II Elements

Type Of Element	Housing Available
R □ F Series and RM □ F Series	See Housing Data Sheets H2, H13, H14, H15, H16, H17, H18, H19, H36, H37, H38 and H39 for Pall housings specifically designed to accommodate these elements. R □ F Series elements may also be used with competitor built housings which accommodate 2 $\frac{1}{2}$ " O.D. x 10", 20", 30", and 40" nominal length elements; however, sealing may be marginal for grades 030 (3 μm absolute) and finer.
AB □ Y Series, Code 3, 7 and 8	See Housing Data Sheets H22, H26, H28, H29, H30, H31, H32, and H35.



2200 Northern Boulevard
East Hills, New York 11548-1289

888.873.7255 toll free
516.484.5400 phone
516.484.0364 fax

Visit us on the web at www.pall.com

Pall Corporation has offices and plants throughout the world in locations including.

© Copyright 2001, 1998, 1986 Pall Corporation. Pall, are trademarks of Pall Corporation. ® Indicates a Pall trademark registered in the USA. Filtration. Separation. Solution.SM is a service mark of Pall Corporation.